

Compressor Information - C76 (G - Generator Optional) (DLT0703 Sold Outside Europe)

Model	C76 (G - Generator Optional) (DLT0703 Sold Outside Europe)
Series	C Series
Description	Portable Compressors (C Series - 3.5 to 7.6 m3/min)
Gas Compressed	Air
Output Free Air Delivery at Rated Pressure (m3 per min)	7.6
Minimum Operating Pressure (Bar g)	5
Max or Rated Operating Pressure (Bar g)	7 to 8
Maximum Operating Pressure (Bar g)	8
Motor Output (kW)	61
Noise Level (db)	101
Length (mm)	3578
Width (mm)	1580
Height (mm)	1390
Compressed Air Outlets (Inches)	3 x 3/4" + 1 x 1 1/2"
Off Load Speed (rpm)	1500
Full Load Speed (rpm)	2600
Oil capacity (l)	14
Weight: Straight towbar, braked (kg)	1069 (1137 for G version)
Weight: Adjustable towbar, braked (kg)	1100 (1168 for G version)
Fuel Tank Capacity (l)	120
Canopy Length (mm)	2050
Engine Type	Deutz BF4M2011
Cooling System	Liquid cooled (oil)

At Rated Operating Pressure (Bar g):	7
Output Free Air Delivery (m3/min):	7.6



Additional Information

The latest CompAir Range of Portable Compressor incorporate the very latest technological advances and manufacturing processes to provide users with a portable supply of economic and reliable compressed air.

Dimensions shown are braked with straight towbar - please see PDF spec sheet for more information and options

Power sound level (dB(A)) acc. to 2000/14/EC 2) ( Legal limiting values of EC directive from 01.2006)

Please see pdf brochure (left) for Electrical generator information

\*images may show a similar model to that stated - please contact [your sales and service provider](#) for pricing and further information.  
Inlet pressure = 1 bar unless otherwise stated