



London - Midlands - Belfast - Glasgow

www.clowgroup.co.uk  
enquiries@clowgroup.co.uk  
0845 130 6272 (UK Local Call Rate)



By Appointment to  
Her Majesty the Queen  
Manufacturers of Access Equipment  
Clow Group Ltd., Glasgow

Clow Group Ltd.

## Clow Light Weight Stagings BS2037 Class 1

Robustly constructed from aluminium box section stiles with either softwood slats or non slip laminated hard wearing construction grade ply board.

Available in both 450mm and 600mm widths, Clow Stagings conform to British Standard BS2037 Class 1 and support a maximum static load of 272kg.

The 600mm staging width conforms with current building regulations allowing these stagings to be used as a direct replacement for standard scaffolding boards.



Clow Stagings are available in lengths from 2.44m to 7.32m, (8ft – 24ft).

Aluminium Staging with Timber Slatted Decking BS2037 Class 1			
450mm Width		600mm Width	
Code	Length	Code	Length
AP8	2.4m (8')	WAP8	2.4m (8')
AP10	3.5m (10')	WAP10	3.5m (10')
AP12	3.66m (12')	WAP12	3.66m (12')
AP14	4.27m (14')	WAP14	4.27m (14')
AP16	4.88m (16')	WAP16	4.88m (16')
AP18	5.49m (18')	WAP18	5.49m (18')
AP20	6.10m (20')	WAP20	6.10m (20')
AP22	6.70m (22')	WAP22	6.70m (22')
AP24	7.32m (24')	WAP24	7.32m (24')

Aluminium Staging with Phenol Anti-Slip Ply Decking BS2037 Class 1			
450mm Width		600mm Width	
Code	Length	Code	Length
AP8WD	2.4m (8')	WAP8WD	2.4m (8')
AP10WD	3.5m (10')	WAP10WD	3.5m (10')
AP12WD	3.66m (12')	WAP12WD	3.66m (12')
AP14WD	4.27m (14')	WAP14WD	4.27m (14')
AP16WD	4.88m (16')	WAP16WD	4.88m (16')
AP18WD	5.49m (18')	WAP18WD	5.49m (18')
AP20WD	6.10m (20')	WAP20WD	6.10m (20')
AP22WD	6.70m (22')	WAP22WD	6.70m (22')
AP24WD	7.32m (24')	WAP24WD	7.32m (24')

Ref:APWAP\_111201