

Tracked Power Dumpers


TD500HL & TD650



HONDA
POWER EQUIPMENT




TD500 HL Hydraulic High-Tip (500kg)



A Overall length	1.96m
B Overall width	0.68m
C Overall height	1.136m
D Maximum height when skip tipped (scissors lowered)	1.960m
E Skip loading height (scissors lowered)	0.7m
F Skip discharge height (scissors lowered)	0.85m
G Forward discharge distance	0.26m
H Skip loading height (scissors raised)	1.128m
J Skip discharge height (scissors raised)	1.226m
K Maximum height skip raised (scissors raised)	2.486m
Machine weight:	317 kg

TD650 NEW Hydraulic Standard Tip (650kg)



A Overall length	1.96m
B Overall width	0.68m
C Overall height	1.136m
D Maximum height when skip tipped	1.34m
E Skip loading height	0.6m
F Skip discharge height	0.82m
Machine weight:	249 kg

LUBRICANTS & CAPACITIES (Total-Fina factory fill)

Hydraulic Oil	Azzola ZS46 (capacity 5 litres)
Grease	Multis EP2
General lubricating oil (pivot pins)	Rubia B20W/30

PRESSURES

Hydraulic Pressure	2500psi (172 bar)
--------------------	-------------------

MAXIMUM PAYLOAD CAPACITY

On level ground	TD500HL 500kgs	TD650 650kgs
On gradients	350kgs	350kgs

MAXIMUM GRADIENT

Maximum Downward Gradient	15°
Maximum Upward Gradient	20°

NOISE LEVELS

Operators Ear	85LPA
Directive 2000/14/EC	101LWA

TRAVEL SPEED

Forward Travel	0-4.3 km/h
Reverse Travel	0-3.6 km/h

VIBRATION AT HANDLEBARS

Hand/Arm Vibration (EN1033)	11 m/s@3600 rpm
-----------------------------	-----------------



Fits through standard doorway > 680mm



Superb Traction



High tip into skips < 1220 mm



Suited to areas where access width is limited



Perfect for Landscaping & Gardening

Seddon
SEDDON PLANT & ENGINEERS LTD

Seddon (Plant & Engineers) Limited, PO Box 41, Plodder Lane, Bolton, BL4 0LS
Tel: 01204 854600, Fax: 01204 854620, email: sales@seddonplant.co.uk, www.seddonplant.co.uk

Due to a policy of continual improvement, the manufacturer reserves the right to change specifications without further notice.