

Technical data

# HD 12 VV



**Tandem rollers Series HD CompactLine**

Tandem roller with two vibrating roller drums

**H230**

**HIGHLIGHTS**

- > Simple transport, simple loading
- > Compact dimensions
- > Excellent view of drum edge, machine and construction site environment
- > Ergonomic driver platform
- > Simple, intuitive and language-neutral control

**TECHNICAL DATA HD 12 VV (H230)**

**Weights**

Operating weight with ROPS	kg lbs	2695 5,942
Operating weight, max.	kg lbs	3410 7,519
Static linear load, front/rear	kg/cm lbs/in	11,1/11,3 62.2/63.3
French classific., data/class		11,3/PV3

**Machine dimensions**

Total length	mm in	2530 99.6
Total height with ROPS	mm in	2475 97.4
Height, loading, min.	mm in	1752 69.0
Wheelbase	mm in	1700 66.9
Total width	mm in	1310 51.6
Max. working width	mm in	1250 49.2
Ground clearance, center	mm in	280 11.0
Curb clearance, left/right	mm in	570/570 22.4/22.4
Turning radius, inside	mm in	2370 93.3

**Drum dimensions**

Drum width, front/rear	mm in	1200/1200 47.2/47.2
Drum diameter, front/rear	mm in	720/720 28.3/28.3
Drum thickness, front/rear	mm in	15/15 0.6/0.6
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	0/50 0.0/2.0

**Diesel engine**

Manufacturer		KUBOTA
Type		D1703
Number of cylinders		3
Power rat. ISO 14396, kW/PS/rpm		18,5/25,2/2200
Power rating SAE J1349, kW/HP/rpm		18,5/24,8/2200
Emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		-

**Drive**

Speed, infinitely variable	km/h mph	10,2 6.3
Climbing ability, vibration on/off	%	30/40

**Vibration**

Vibration frequency, front, I/II	Hz vpm	65/51 3,900/3,060
Vibration frequency, rear, I/II	Hz vpm	65/51 3,900/3,060
Amplitude, front, I/II	mm in	0,45/0,45 .018/.018
Amplitude, rear, I/II	mm in	0,45/0,45 .018/.018
Centrifugal force, front, I/II	kN lbs	38/23 8,550/5,175
Centrifugal force, rear, I/II	kN lbs	38/23 8,550/5,175

**Steering**

Oscillation angle +/-	°	8
Steering, type		Articulated steering

**Sprinkler system**

Water sprinkler, type		Pressure
-----------------------	--	----------

**Tank capacity/Fill capacity**

Fuel tank, capacity	L Gal	42 11.1
Water tank, capacity	L Gal	180 47.6

**Sound level**

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power LW(A), measured	db(A)	104

**EQUIPMENT**

12 V outlet | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling with interval switch | Operator's platform with entry from both sides | Left and right drive lever | Mechanical battery isolation switch | Vibration-isolated operator's platform | Track offset, mechanical | Automatic vibration system | Water filtering (triple) | Central lifting bracket | Central water drain

**OPTIONAL EQUIPMENT**

Plastic scraper, foldable | ROPS, foldable | Protective roof, plastic tarpaulin | Edge pressing and cutting equipment | Back-up alarm | Working light | Battery isolation switch operated with external activation | V-belt protection