

Aerial Work Platforms » Diesel Powered Scissor Lifts » Diesel Powered Liftlux » 210-25

210-25

Diesel Powered Scissor Lifts Diesel Powered Liftlux

Features

- Full width platform with hydraulic-powered deck extension provides large workspace
- Standard four wheel drive with high angle steering for excellent mobility
- Driveable up to maximum platform height for enhanced productivity

Quick Specs

- Platform Height Elevated – 21.00 m
- Overall Width – 2.50 m
- Platform Capacity – 1000 kg



210-25 Specifications

Performance Data

Platform Capacity	1,000 kg
Capacity on Extension	800 kg
Deck Extension	Hydraulic
Lift/Lower Time	100/75 seconds
Maximum Drive Height	21.00 m
Weight*	15,000 kg
Ground Bearing Pressure**	kg/cm ²
Drive Speed (Lowered)	2.3 km/h
Gradeability	30%
Turning Radius - Inside	1.50 m
Turning Radius - Outside	6.20 m
Tyre Size	315/80 R22.5

Tyre Type	Foam Filled Lug Tread
------------------	-----------------------

Power System/Chassis

Axle Oscillation	15cm
Brakes	Spring Applied
Diesel Engine	Deutz D2011L04i (42kW)
Fuel Tank Capacity	90 L
Hydraulic Reservoir	260 L

Dimensions

Platform Height - Elevated	21.00 m
Platform Height - Lowered	3.00 m
Platform Railing Height	1.10 m
Stowed Height (Rails Folded)	3.20 m
Platform Dimensions	2.50 m x 5.35 m
Platform Length Fully Extended	7.55 m
Overall Length	5.75 m
Overall Width	2.50 m
Wheelbase	3.90 m
Ground Clearance	0.26 m